

AMENDMENTS TO THE CLAIMS:

Please cancel claim 1 – 6, 12 – 15, 19 and 25 and amend claims 7, 8, 9 and 16 as follows:

1-6. (Canceled)

7. (Currently Amended) An apparatus for supplying recirculated exhaust gases to incoming air of a piston-type internal combustion engine, said apparatus comprising:

a duct (2) for incoming air and a feed pipe (1) for exhaust gases and which includes ~~opens out into~~ an outlet section (3) inside the duct (2);

said outlet section (3) comprising at least one outlet (4) for distributed supply of exhaust gases and said outlet section (3) constitutes an outlet path (a) that extends in the longitudinal direction of the duct (2) and the length of which is longer than an inner diameter of the feed pipe (1), wherein the at least one outlet (4) is ~~The apparatus as recited in claim 6, wherein a~~ plurality of elongated outlets (4) ~~are~~ distributed along a circumference running transversely to the motional direction of incoming air in the form of substantially parallel slots in the longitudinal direction of the duct (2); and

said outlet path (a) has a length that is at least twice as long as the inner diameter of the feed pipe (1) whereby it is possible for an exhaust-gas pulse transported through the feed pipe (1) to be distributed into a portion (a1) of incoming air which, in the duct (2), passes the outlet section (3).

8. (Currently Amended) An apparatus for supplying recirculated exhaust gases to incoming air of a piston-type internal combustion engine, said apparatus comprising:

a duct (2) for incoming air and a feed pipe (1) for exhaust gases and which includes ~~opens out into~~ an outlet section (3) inside the duct (2);

said outlet section (3) comprising at least one outlet (4) for distributed supply of exhaust gases and said outlet section (3) constitutes an outlet path (a) that extends in the longitudinal direction of the duct (2) and the length of which is longer than an inner diameter of the feed

pipe (1), wherein the at least one outlet (4) is ~~The apparatus as recited in claim 6, wherein~~ at least one elongated outlet (4) ~~extends~~ extending along a circumference running transversely to the motional direction of incoming air in the form of a helical slot; and

said outlet path (a) has a length that is at least twice as long as the inner diameter of the feed pipe (1) whereby it is possible for an exhaust-gas pulse transported through the feed pipe (1) to be distributed into a portion (a1) of incoming air which, in the duct (2), passes the outlet section (3).

9. (Currently Amended) An apparatus for supplying recirculated exhaust gases to incoming air of a piston-type internal combustion engine, said apparatus comprising:

a duct (2) for incoming air and a feed pipe (1) for exhaust gases and which includes ~~opens~~ ~~out into~~ an outlet section (3) inside the duct (2);

said outlet section (3) comprising at least one outlet (4) for distributed supply of exhaust gases and said outlet section (3) constitutes an outlet path (a) that extends in the longitudinal direction of the duct (2) and the length of which is longer than an inner diameter of the feed pipe (1), wherein the at least one outlet (4) is ~~The apparatus as recited in claim 6, wherein~~ at least one elongated outlet (4) ~~extends~~ extending along a circumference running transversely to the motional direction of incoming air in the form of a plurality of substantially parallel helical slots; and

said outlet path (a) has a length that is at least twice as long as the inner diameter of the feed pipe (1) whereby it is possible for an exhaust-gas pulse transported through the feed pipe (1) to be distributed into a portion (a1) of incoming air which, in the duct (2), passes the outlet section (3).

10-15. (Canceled)

16. (Currently Amended) A process for supplying recirculated exhaust gases to incoming air to a piston-type internal combustion engine, which internal combustion engine comprises a duct (2) for incoming air and a feed pipe (1) including an outlet section (3) for said exhaust gases, the

supply of the exhaust gases to the duct (2) being distributed over an outlet path (a) which is extended in the longitudinal direction in of the duct and the length of which is longer than the inner diameter of the feed pipe (1), the length of the outlet path (a) extended in the longitudinal direction of the duct is at least ~~20%~~ 80% of the path the incoming air will be displaced along in the duct (2) during the period between two successive exhaust-gas pulses from said internal combustion engine.

17-19. (Canceled)

20. (Original) The process as recited in claim 16, wherein the length of the outlet path (a) extended in the longitudinal direction of the duct is approximately 100% of the path of the incoming air.

21. (Original) The process as claimed in claim 16, wherein the length of the outlet path (a) extended in the longitudinal direction of the duct is approximately as long as the path the incoming air will be displaced along in the duct (2) during the period between two successive exhaust-gas pulses in the flow of said recirculated exhaust gases.

22. (Original) The process as claimed in claim 21, wherein the supply of the exhaust gases to the duct (2) is also distributed along a circumference running transversely to the motional direction of incoming air.

23. (Original) The process as claimed in claim 22, wherein the supplied exhaust gases are re-mixed in the duct (2) with the aid of at least one turbulator device.

24. (Original) The process as claimed in claim 22, wherein the supplied exhaust gases are re-mixed in the duct (2) with the aid of at least one venturi device.

25. (Canceled)

26. (Previously Presented) A process for supplying recirculated exhaust gases to incoming air to a piston-type internal combustion engine, which internal combustion engine comprises a duct (2) for incoming air and a feed pipe (1) for said exhaust gases, the supply of the exhaust gases to the duct (2) is also distributed along a circumference running transversely to the motional direction of incoming air to be distributed over an outlet path (a) which is extended in the longitudinal direction of the duct and the length of which is longer than the inner diameter of the feed pipe (1), the length of the outlet path (a) extended in the longitudinal direction of the duct is approximately as long as the path the incoming air will be displaced along in the duct (2) during the period between two successive exhaust-gas pulses in the flow of said recirculated exhaust gases.